



JOHN DEERE

n Head

JOHN

# DEERE INSPECTION

					HEADER INFORMATION		
Name:					Header Type:		
Address:					Serial Number:		
City and State:					Warranty End Date:		
Phone:					Date:		
Snouts	CONDITION			Customer OK's Repair	New Specification	Replacement Specification	Comments
	OK	Repair / Replace	Needs Adjusted				
Points							
Snouts							
End Snout Dividers							
Ear Savers							
Shields							
Height Sensors & Wiring							
Auger	CONDITION			Customer OK's Repair	New Specification	Replacement Specification	Comments
	OK	Repair / Replace	Needs Adjusted				
Auger Tube							
Flighting					Clearance of 22 mm (7/8 in) from the flighting to the floor		
Paddles							
Bearings							
Drive Chain							
Drive Chain Sprockets							
Floor Sheets							
Auger Stripper					Clearance of 6 mm (1/4 in) from flighting to stripper		

Row Units	CONDITION			Customer OK's Repair	New Specification	Replacement Specification	Comments
	OK	Repair / Replace	Needs Adjusted				
Frames							
Row Unit Gearcases							
Slip Clutches							
Spring					66 mm (2 5/8 in)		
Trash Knives					1.5 mm (1/16 in) Clearance to stalk roll flutes		
Fixed Deck Plates							
Adjustable Deck Plates							
Error Codes							
Calabration							
Wiring							
Sensor							
Gathering Chains							
Guides							
Sprockets							
Bushing, Spring & Bolt					5 mm(3/16 in) Clearance between spacer tube and washer		
Stalk Rolls							
Seals							
Needle Bearings							
Shims							
Ball Bearings							
Shaft							
Drive Chain							
Sprockets							
Oil level							

